

INTRODUCTION

- · Strengthened cartridge seals.
- All single phase motors are fitted with thermal motor protector.
- · Good compatibility and environment friendly.
- Enhanced hydraulic efficiency and low power consumption.
- . Low noise and vibration level.
- Light-Weight & Easy handling
- . CED Coating parts for corrosion resistance that comes with an uniform coating, which provides 5 times more protection over conventional painting, resulting in longer life.
- · Suitable for slightly aggressive liquids

APPLICATIONS

Washing System

- Industrial Plants
- Cooling and air conditioning system
 Boiler feeeding system
- Water treatment system
- · Irrigation system.
- Fire Fighting System
- Water Supply

PERFORMANCE

SPECIFICATION

Head Range, H: Max. 220 Meters Max. 8.5 m³/hr (142 LPM) Flow Range, Q : 1.5 Kw - 3.7 kW Power Range : Supply Voltage : 3 PH x 380-415 V 1 PH x 220-230/240 V

Pump Shaft DUPLEX Impeller SS 304 Mechanical Seal Cartridge Type Suction/Discharge Chamber : CI FG 260

IE3 Efficiency Class : Insulation **H Class** IP55 Protection

PERFORMANCE TABLE

I LIN ONNOUTOL MIDEL											
PUMP SET SCRM 4 LEAFLET DATA SHEET											
			M³/Hr.	1	2.2	3.2	4.0	4.5	5.0	6.0	8.5
			L/Min.	17	37	53	67	75	83	100	142
S.NO.	MODEL- STAGE	MOTOR	RATING TOTAL HEAD IN (M)								
		[kW]	[HP]	TOTAL FILAD IN (III)							
1	SCRM4-8	1.5	2	85	70	75	71	67	63	51	6
2	SCRM4-15	3.7	5	160	148	140	132	119	101	76	7
3	SCRM4-18	3.7	5	190	174	165	159	144	119	91	8
4	SCRM4-21	3.7	5	220	198	190	184	166	138	96	8

India: Toll Free No. 1800 103 5555 Other Countries: +91-7292 410500

SHAKTI PUMPS (INDIA) LIMITED

Plot No. 401, 402, & 413, Industrial Area, Sector - 3, Pithampur - 454774, Dist. - Dhar, (M.P.) - INDIA, E-mail: info@shaktipumps.com,

Visit us at: www.shaktipumps.com

Authorised Dealer / Distributor :





SHAKTI SCRM 4 PUMP



SHAKTI

THE POWER OF INNOVATION, EFFICIENCY & TECHNOLOGY.

Best Suitable Application







