



SIMHA 2.0 UNIVERSAL DRIVE

Leading a New Start



SUPPORTS WIDE VARIETY OF MOTORS



DUST-PROOF & RAIN-PROOF IP 65 DESIGN



PLUG & PLAY SHOCK-PROOF CONNECTORS



POWERED WITH REMOTE MONITORING SYSTEM





GRAPHICAL LCD FOR EASY OPERATION



WIDE TEMPERATURE RANGE



INDEPENDENT DATA LOGGING FACILITY



MOBILE APP CONTROL

Shakti's Simha Universal Drive is a unique product designed, developed and manufactured in India. This drive makes it possible to run industrial motor pump sets. It supports wide varieties of motors by virtue of its universal design. It's IP 65 design and rust-proof metallic enclosure provides protection from foreign particles (e.g. rain, dust, oil) which obsoletes the need for extra outer case. Therefore, this product is recommended by experts for it's unique features, efficiency, zero operating cost, plug and play installation, electrically safe user handlings and longer period of warranty.

Suitable for Industrial Fan



Suitable for HVAC System Suitable for Conveyor Belt

APPLICATION

All in one solution for driving of various motors like AC-IM, PMSM, IPMSM, S4RM, etc.

TECHNICAL SPECIFICATION

Product			
Power	0.75/1/2 HP	3/5 HP	7.5/10 HP
	960000098	9600000095	9600000097
Input (DC)			
AC Voltage range (if applicable)	90-245 VAC (1-φ)	200-440 VAC (3-□)	360-460 VAC (3-□)
Output (AC)			
Nominal AC Voltage Range	0-245 VAC	0-415 V	
Frequency	0-200Hz		
Max. AC current	12 20		20
Rated Power at AC Side	1700 W	2900 W	9300 W
Power Factor	0.7-0.9 at full load		
THD-	70-150%	70-150%	70-150%
slope-	4000 V/uS	7200 V/uS	7200 V/uS
Peak-	400 V	750 V	750 V
Connection Phases		•	
Efficiency			
Max. Efficiency	>93%	>95%	>97%
General Data			
Protection	Short Circuit, Lighting/Surge, Over Temprature, Over Current, Over Voltage, Dry Run		
Ingress Protection	IP 65		
Certificates	IEC 61683, IEC 600682-2- (1,2,14,30), IS 16221-2(IEC 62109-2), IEC 60529, EN 50530		
Operating Temperature Range	-20°C to 70°C (45°C to 70°C with derating)		

WHY TO CHOOSE SHAKTI'S SIMHA 2,0 UNIVERSAL DRIVE

OTHER DRIVES	SIMHA 2.0 UNIVERSAL DRIVE	
Relatively difficult installation & operation	Simple installation & operation with graphical LCD	
Confusing connections with possibility of shock	Plug and play shock-proof connectors with unique connection	
IP 20	IP 65 (Protection from dust and rain)	
Remote Monitoring System (RMS) not available	Remote Monitoring System (RMS) inbuilt	
Independent Data Logging Facility not available	Independent Data Logging Facility available	
Mobile Application Facility not available	Mobile Application Facility available	

India: Toll Free No. 1800 103 5555 Other Countries: +91-7292 410500

SHAKTI PUMPS (INDIA) LIMITED

Sector - 3, Pithampur - 454774, Dist. - Dhar, (M.P.) - INDIA. Tel.: +91-7292 410500, E-mail: info@shaktipumps.com, Web: www.shaktipumps.com



