



DESH KA PUMP SHAKTI PUMP



SELF PRIMING PUMPS
CRP S51 Series

FEATURES

- Suitable for wide voltage operation - 160 to 240 V
- Brass forged Impeller
- High quality mechanical seal
- Double shielded ball bearings – no need of additional lubrication
- TEFC capacitor start and run type motor and no need of centrifugal switch
- High quality enameled copper wire
- Fitted with T.O.P (thermal overload protector) for safety of motor
- Self priming upto 30 ft of suction lift
- Pump Light weight for easy handling
- Compact design



Toll Free Number: 1800 103 5555

Shakti Self Priming Pumps CRP S51 Series

APPLICATIONS:

- Residential Bungalows, Apartments, etc.
- Gardening and small plants
- Solar Heater Systems
- Lawn Sprinklers, Small farms
- Car washing
- Booster applications
- Small fountains

TECHNICAL SPECIFICATION :

Power Rating	: 0.37 kW / 0.75 kW
Head Range	: 6 – 60 m
Capacity	: 300 – 3200 LPH
Voltage	: 160 - 240V (1PH)
Liquid	: Clear Water
Operating Temp.	: 40 °C

MATERIAL OF CONSTRUCTION :

Motor Body	: Aluminum Extruded
Impeller	: Forged Brass
Delivery Casing	: Cast Iron
Bracket, E.Cover	: Cast Iron
Shaft	: Carbon / Stainless Steel

PERFORMANCE CHART

Model	kW / HP	Pipe Size (mm)	Discharge in LPH	Total Head in Metres												
				6	9	12	15	18	21	24	27	30	33	36	39	42
CRP S51 /PRE 0.5HP	0.37 / 0.5	25x25		3000	2900	2650	2400	2100	1850	1600	1300	1000	700	350	300	250

SHAKTI PUMPS (I) LTD.

Sector - 3, Pithampur - 454774, Dist. - Dhar (M.P.) - INDIA
Tel.: +91-7292-410500 Fax: +91-7292-410519,
E-mail: info@shaktipumps.com, sales@shaktipumps.com
Web: www.shaktipumps.com

Authorised Dealer / Distributor :